



### TYPICAL APPLICATIONS

Bituminous resurfacing  
Milling operations  
Utility operations  
Shoulder operations

### SYMBOLS



Work area



Sign on portable or permanent support



Flagger with traffic control sign

### GENERAL NOTES

This Standard is used where at any time, any vehicle, equipment, workers or their activities require an intermittent or continuous moving operation on the pavement where the average speed of movement is greater than 2 km/h (1 mph) and less than 6 km/h (4 mph).

\* Minimum distance is 60 m (200'). Maximum distance to be determined by the Engineer but should not exceed 1/2 the length required for one normal working day's operation or 3200 m (2 miles), which is less.

If the operation does not exceed 60 minutes, traffic control may be in conformance with Standard 701301.

All dimensions are in millimeters (inches) unless otherwise shown.

Illinois Department of Transportation	
APPROVED January 1, 1997	ISSUED 1-1-97
ENGINEER OF OPERATIONS	
APPROVED January 1, 1997	
ENGINEER OF DESIGN AND ENVIRONMENT	

DATE	REVISIONS
1-1-97	Renum. Standard 2306-10. Deleted orange flags and FRESH OIL sign.
5-1-95	Rev. FLAGGER sign and flagger symbols to be filled in.

LANE CLOSURE 2L, 2W  
SLOW MOVING OPERATIONS-DAY ONLY  
FOR SPEEDS  $\geq$  45 MPH

**STANDARD 701306**